









XFE 75W-90 Syntheti

## Spicer®XFE 75W-90

# Extra Fuel-Efficient Synthetic Gear Lubricant

2.5% fuel savings.
Unparalleled performance.

Our most fuel-efficient gear lubricant to date, Spicer® XFE 75W-90 delivers fuel savings that will make a noticeable impact on your bottom line. Engineered to meet the specifications of linehaul, vocational heavy-duty axles, and light-duty axles. You will still experience longer gear life and better operating performance, even in extreme temperatures. You can enjoy a 2.5% fuel savings improvement over standard 75W-90 oil, and extend the warranty on your Spicer heavy-duty or medium-duty carriers (see back for more details).



### **Spicer® XFE 75W-90 Extra Fuel-Efficient**

# Synthetic Gear Lubricant

### **Advantages and Benefits:**

- Quantifiable 2.5% fuel savings improvement over 75W-90 oil\* - calculate the savings at www.SpicerParts.com/fuelsavings
- Reduced gear wear
- Reduced maintenance
- · Less oil disposal
- Decreased vehicle downtime
- · Excellent seal compatibility
- · Maximum extreme hot and cold temperature performance
- Extended drain interval up to 500,000 miles
- Extended warranty protection

Size	Part Number
1-gallon container	XFE75W90-G
5-gallon pail	XFE75W90-P
55-gallon drum	XFE75W90-D

### **Specifications/0EM Approvals**

Spicer® XFE 75W-90 extra fuel-efficient synthetic gear lubricant is approved to meet the most stringent industry specifications, as established by Dana:

- Dana SHAES 256 Rev C
- Dana SHAES 429
- SAE J2360; API MT-1 and API GL-5
- Meritor O76-N
- Mack Truck Go-J Plus
- Navistar MPAPS B6821

### **Get an Extended Warranty When You Purchase** Spicer® Gear Lube!

Purchase a new heavy-duty or medium-duty Spicer service carrier for your linehaul vehicle and fill it with Spicer® XFE 75W-90 extra fuel-efficient synthetic gear lubricant. When doing so, you can extend your 2-year unlimited warranty by an additional 12 months for a total of 3 years. For more details on how to register for this extended warranty, visit our website at www.SpicerParts.com/carriers.

### **Characteristics:**

Properties	Unit	Typical Value	Method
SAE class	75W-90	SAE J 306	
Density at 15.6 °C	lbs/gal	0.864 (7.21)	ASTM D 1298
Viscosity index at 100° C at 40° C at -40° C	- mm <sup>2</sup> /s mm <sup>2</sup> /s mPas	169 15.2 95.4 45, 100	ASTM D 2270 ASTM D 445 ASTM D 445 ASTM D 2983
Flash Point	°C	210	ASTM D 92
Pour Point	°C	-57	ASTM D 97

NOTE: Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally.

> Calculate the savings at www.SpicerParts.com/fuelsavings.

To learn more about Spicer® XFE 75W-90 extra fuel-efficient synthetic gear lubricant and other genuine Spicer products, visit www.SpicerParts.com today!

<sup>\*</sup> Fuel savings based on initial results of applications tested. Results may vary.



Dana Aftermarket Group

Form # SPR-XFE-SS-82015 Copyright Dana Limited, 2015. All rights reserved. Dana Limited. Printed in U.S.A.











